

Use MiniPCI in
standard
PCI sockets!

MiniPCI v1.0 and
PCI v2.1, v2.2
standards compliant

Use wireless MiniPCI cards
in standard PCI platforms

Two LEDs connected to
MiniPCI

MiniPCI Adapter RouterBOARD 11 (IA/MPI1)

MikroTik's RouterBOARD 11 MiniPCI to PCI adapter is an advanced adapter for 3.3v MiniPCI to PCI standard sockets. The adapter is provided in PCI card form with an integrated MiniPCI slot that allows you to use MiniPCI cards in standard PCI sockets. The MiniPCI adapter includes two LEDs connected to the MiniPCI (according to standards).



Specifications

Standards:	MiniPCI v1.0 standard compliant; PCI v2.1 and v2.2 compliant
Operation Voltage:	PCI 3.3v and 5v support; optional - 3.3v only support (factory option - RouterBOARD 11-3.3)
Input Power:	Up to 5w of 3.3v power supplied to MiniPCI card; optional - 3.3v (5w) out header (factory option - RouterBOARD 11-h)
LED:	Two LEDs connected to MiniPCI (according to standards)
Operation Temp.:	0° C to 70° C
Storage Temp.:	-20° C to 80° C
Humidity Range:	0% to 90%
Mounting:	Mounting for optional tin shield
Connector:	Traces for antenna out connector (contact sales for this factory option)
Dimension:	122 x 96 x 8 mm

For ordering information, contact sales@mikrotik.com